



# Polyester Tape

## 8992/8992L

Technical Data

July, 2014

**Product Description** 3M™ Polyester Tape 8992 is a dark green polyester tape with silicone adhesive. It can be used in a large variety of high temperature applications including powdercoat masking, flashbreaker, and bag sealing applications. Additional applications include, splicing, tabbing, or roll closing silicone treated liners or materials.

Product Construction	Backing	Adhesive	Liner (8992L)	Color	Standard Roll Length
	Polyester	Silicone	Polyester	Dark Green	72 yds. (65.8 m)

### Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	44 oz./in. width (48 N/100 mm)	D-3330
Tensile Strength:	37 lbs./in. width (842 N/100 mm)	D-3759
Elongation at Break:	46%	D-3759
Backing Thickness:	2.0 mils (0.052 mm)	D-3652
Total Thickness:	3.2 mils (0.082 mm)	D-3652
Liner Thickness (8992L):	3.0 mils (0.075 mm)	D-3652
Temperature Use Range:	Up to 400°F (204°C)	

### Features

- Polyester films offer excellent thermal, abrasion, and chemical resistance while maintaining their flexibility.
- Green color makes tape placement obvious for both application and removal.
- Backing leaves a sharp paint line.
- Silicone adhesives offer high heat resistance compared to many rubber and acrylic adhesives, reducing failure due to softening, oozing, and adhesive transfer.
- Silicone adhesives adhere well to tough-to-stick-to surfaces like silicone liners and fixtures coated with mold release.
- Silicone adhesive removes cleanly from many surfaces.
- Lined version available for die-cuts.

### Application Ideas

- Masking for powdercoat painting.
- Flashbreaker tape when pulling through cured coating such as epoxies.
- Holding and splicing difficult to stick to surfaces such as silicone liner.
- Holding parts or sealing vacuum bags during processing.