

www.heskins.com SAFETY DATA SHEET 02/10/2015

### H3502

# According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010.

#### SECTION I: Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier** 

Product name H3502

Product number H3502

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive

Uses advised against No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

Supplier HESKINS LTD CHURCHILL ROAD INDUSTRIAL ESTATE BRINSCALL PR6 8RQ T: +44 (0) 1254 832266 F: +44 (0) 1254 832476 E: mail@heskins.com

#### **I.4. Emergency telephone number**

Emergency telephone +44 (0)1254 832266 (NOT 24HRS)

**SECTION 2: Hazards identification** 

#### 2.1. Classification of the substance or mixture

#### Classification

ISO 9001

9

ISO 14001

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36. F;R11. R66,R67.

\_\_\_\_\_



#### www.heskins.com

02/10/2015

**Physicochemical** The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

#### 2.2. Label elements

#### Pictogram



#### Hazard statements

H225 Highly flammable liquid and vapour.H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

#### Contains

BUTANONE, ACETONE, ETHYL ACETATE

#### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

#### **SECTION 3: Composition/information on ingredients**

3.2. Mixtures BUTANONE CAS number: 78-93-3

EC number: 201-159-0

32.5% REACH registration number: 01-2119457290-43

**Classification** Flam. Liq. 2 - H225

Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67

Eye Irrit. 2 - H319



# HESKINS

ISO 14001

mail@heskins.com	www.heskins.com	02/10/2015
STOT SE 3 - H336		
ACETONE		27.0%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01- 2119471330-49
Classification		
Flam. Liq. 2 - H225	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67	
Acute Tox. 4 - H312		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
ETHYL ACETATE		22.5%
CAS number: 141-78-6	EC number: 205-500-4	REACH registration number: 01- 2119475103-46-0017
Classification		
Flam. Liq. 2 - H225	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67	
Eye Irrit. 2 - H319	F,NIT AI	,00 001 001
STOT SE 3 - H336		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

**Inhalation** Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Ingestion Rinse mouth thoroughly with water. Get medical attention.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

**Eye contact** Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

\_\_\_\_\_

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Prolonged skin contact may cause redness and irritation.



www.heskins.com

Eye contact May cause temporary eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** The product is flammable. Heating may generate flammable vapours. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. The product is highly flammable.

#### Hazardous combustion products

Does not decompose when used and stored as recommended.

#### 5.3. Advice for firefighters

## Protective actions during firefighting

Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes.

#### Special protective equipment

for firefighters

Wear chemical protective suit.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.





#### www.heskins.com

#### 6.4. Reference to other sections

mail@heskins.com

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

Storage class Flammable liquid storage.

#### 7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

#### **SECTION 8: Exposure Controls/personal protection**

#### 8.1. Control parameters

#### **Occupational exposure limits**

#### BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m3(Sk)

#### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

#### ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm Short-term exposure limit (15-minute): WEL 400 ppm

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

BUTANONE (CAS: 78-93-3) Ingredient comments WEL = Workplace Exposure Limits





www.heskins.com

02/10/2015

mail@heskins.com **ACETONE (CAS: 67-64-1)** Ingredient comments WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

Protective equipment



#### Appropriate engineering

**Controls** Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

**Eye/face protection** The following protection should be worn: Chemical splash goggles.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Hygiene measures Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands after handling. Eating, smoking and water fountains prohibited in immediate work area.

**Respiratory protection** In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type AX. Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **SECTION 9: Physical and Chemical Properties**

#### 9.1. Information on basic physical and chemical properties

Appearance Coloured liquid.

Colour Various colours.

Odour Acetone.





mail@heskins.com Odour threshold Not available. www.heskins.com

02/10/2015

pH Estimated value. pH (concentrated solution): 7-8

Melting point Not available.

Initial boiling point and range 56°C @ 20

Flash point Estimated value. -19°C

Evaporation rate Not determined.

**Evaporation factor** Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits Estimated value. : 1.8%-13%

**Other flammability** Not available.

Vapour pressure Not available.

Vapour density Not available.

Relative density 0.86 @ 20°C

Bulk density Not available.

Solubility(ies) Insoluble in water.

Partition coefficient Not available.

Auto-ignition temperature Estimated value. 515°C

**Decomposition Temperature** Not available.

Viscosity Kinematic viscosity > 20.5 mm<sup>2</sup>/s. Explosive properties Not available.

**Explosive under the influence of a flame** Not considered to be explosive.

Oxidising properties Not available.

**Comments** Information given is applicable to the product as supplied.

9.2. Other information





#### ANTI-SLIP SOLUTIONS

#### mail@heskins.com

www.heskins.com

02/10/2015

Other information No information required.

**Refractive index** Not available.

Particle size Not available.

Molecular weight Not available.

Volatility Not available.

Saturation concentration Not available.

Critical temperature Not available.

Volatile organic compound This product contains a maximum VOC content of 700 g/l.

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

**Stability** No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not applicable. Not relevant.

#### 10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

#### 10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

#### 10.6. Hazardous decomposition products

#### Hazardous decomposition products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

\_\_\_\_\_

#### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

ISO 14001

9

 $\Delta \mathbf{T}$ 

ISO 9001



ANTI-SLIP SOLUTIONS

#### www.heskins.com

02/10/2015

mail@heskins.com

Toxicological effects No information available. Other health effects There is no evidence that the product can cause cancer. Acute toxicity – oral ATE oral (mg/kg) 6,153.85

Acute toxicity - dermal ATE dermal (mg/kg) 6,153.85

Acute toxicity - inhalation ATE inhalation (vapours mg/l) 61.54

Serious eye damage/irritation Serious eye damage/irritation Irritation of eyes is assumed.

**Respiratory sensitisation Respiratory sensitisation** Not determined.

Skin sensitisation Skin sensitisation Not determined.

Carcinogenicity Carcinogenicity Data lacking.

Target organ for carcinogenicity Not relevant.

**Reproductive toxicity Reproductive toxicity - fertility** Not available.

**Reproductive toxicity development** This substance has no evidence of toxicity to reproduction.

#### Aspiration hazard Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure. General information No specific health hazards known.

Inhalation Vapour from this product may be hazardous by inhalation.

**Ingestion** May be harmful if swallowed.

Skin contact May be harmful in contact with skin.

Eye contact May cause blurred vision and serious eye damage.

Toxicological information on ingredients.

#### BUTANONE





mail@heskins.com Acute toxicity - oral www.heskins.com

02/10/2015

Acute toxicity oral (LD<sub>50</sub>mg/kg) 2,000.0

Species Rat

Acute toxicity - dermal Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

Acute toxicity - inhalation Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 20.0

Species Rat

#### **SECTION 12: Ecological Information**

#### 12.1. Toxicity

**Toxicity** The product is not believed to present a hazard due to its physical nature. **12.2. Persistence and degradability** 

#### 12.3. Bioaccumulative potential

Partition coefficient Not available.

#### 12.4. Mobility in soil

ISO 14001

\$

A C S

ISO 9001

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

#### **Ecological information on ingredients.**

#### **BUTANONE**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate Easily from all surfaces.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### Ecological information on ingredients.



#### www.heskins.com BUTANONE

02/10/2015

## Results of PBT and vPvB

**Assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

Other adverse effects None known. Ecological information on ingredients.

#### **BUTANONE**

Other adverse effects None known.

#### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

#### **SECTION 14: Transport information**

14.1. UN number UN No. (ADR/RID) 1133 UN No. (IMDG) 1133 UN No. (ICAO) 1133 UN No. (ADN) 1133

14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** ADHESIVES

**Proper shipping name (IMDG)** ADHESIVES

Proper shipping name (ICAO) ADHESIVES Proper shipping name (ADN) ADHESIVES

#### 14.3. Transport hazard class(es)

ADR/RID class 3 ADR/RID classification code FI ADR/RID label 3 IMDG class 3 ICAO class/division 3 ADN class 3

**Transport labels** 





www.heskins.com

02/10/2015



14.4. Packing group

ADR/RID packing group || IMDG packing group || ADN packing group || ICAO packing group ||

14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant** No.

14.6. Special precautions for user

EmS F-E, S-D

ADR transport category 2 Emergency Action Code •3YE Hazard Identification Number (ADR/RID) 33 Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** Health and Safety at Work etc. Act 1974 (as amended). The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).

**EU legislation** Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).





www.heskins.com

02/10/2015

Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### **SECTION 16: Other information**

Issued by Compliance Revision date 20/07/2015 Revision 20 Risk phrases in full R11 Highly flammable. R36 Irritating to eyes. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.

#### Hazard statements in full

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.

Store Between Store Between 5'c - 25'c

