

Head Office: Unit 1 Coronation Business Park Hard Ings Road Keighley West Yorkshire BD21 3ND

Tel: 01535 610373

Email: sales@vikingtapes.co.uk www.vikingtapes.co.uk

Technical Data Sheet

Product:

Printed Self-Adhesive Mono Reinforced Paper

Typical Applications

- · Heavy duty carton sealing
- Security tamper evident
- · Alternative to water activated tape


Advantages & Benefits

- · Highly aggressive adhesive
- · High tensile strength
- Printed up to 4 Colours
- Excellent adhesion

Construction

- Paper backing with mono weave glass fibre reinforcement
- Synthetic rubber (Hot Melt) adhesive
- Available unprinted and printed up to 4 colours.
- Widths available 36mm to 144mm
- Lengths available 50m to 500m
- Paper colour Brown

CONSTRUCTION



*Lead times may vary depending on number of colours printed. Minimum order quantities apply

Brown

Technical Data

Measure	Unit	Result & Tolerance	
Total Weight (With Glass Fibre)	GSM	110 +/- 5%	
Adhesive Coat Weight	GSM	33 +/- 5%	
Total thickness	Microns	125 +/- 5%	
Peel adhesion (Afera 5001)	Newtons/25mm	11 +/- 5%	
Elongation (Afera 5004)	%	<5	
Tensile Strength (Afera 5004)	Newtons/cm	55 +/- 5%	

Additional information

Tape performance is guaranteed for the first 6 months. Product must be stored at ambient temperature (Between 18c-23c), in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the batch identification number printed on the box. For optimum performance stock <u>should</u> be rotated and used within 12 months. The tapes have adhesive that are pressure sensitive so must be properly applied to ensure the best performance.

Physical and performance characteristics shown above are obtained following tests recommended by AFERA and PSTC. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.