

# Technical

# **Scapa 3162**

## Waterproof Cloth Tape - 0.18mm

### DESCRIPTION

Scapa 3162 is a premium quality, higher adhesion version, polyethylene laminated waterproof cloth tape. It is coated with a pressure sensitive, natural rubber resin adhesive. Scapa 3162 is available in black, white and silver as standard.

### APPLICATIONS

- Designed as a general purpose waterproof cloth tape for applications requiring additional strength and adhesion.
- Used for sealing, bundling, short term masking and protecting.
- Excellent for jointing polyethylene sheeting in asbestos removal applications.
- Switable for double glazing unit sealing.
- Medium temperature duct sealing.
- Carpet joining and edging.

### PRODUCT BENEFITS

- Good water resistance.
- Excellent adhesion and ultimate bond strength.
- Florible and conformable.
- Sorvice temperature: -15°C to +75°C.
- Good all purpose product.
- · Farrunwind.
- Easy tear by hand.
- · Goodinitial tack
- Good low temperature performance for winter applications
- R<sup>®</sup> ©CH and RoHS compliant

Version: 27

Generated Date: 24 October 2022

Page: 1 of 2

www.scap.com

Product Code: 3162

### TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesian to Backing	3.5	N/cm	IEC 60454-2
Adha in to Steel	6.0	N/cm	IEC 60454-2
Break in Strongth	35	N/cm	IEC 60454-2
Thickers	0.18	mm	AFERA 5006*

### STANDARD PRESENTATIONS

- Core: Scapa cardboard core as standard
- Packaging: Bulk packed with interleaving between layers or shrink wrapped in packs of 4 \*
- Pillergih: 50m
- 10 Middh: 10 and 75mm as standard. Other sizes on request.
- \* () up.: Available in silver, black and white as standard

### Note:

\* 50/75mm width rolls

### RECOLLATIONS

The rest should be stored flat on their cut edges in the original packaging, until required for use. The production be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climatic environment, but under these conditions it is recommended the product should be used within two years from date of manufacture.