

Technical Data Sheet

Head Office: Unit 1 Coronation Business Park Hard Ings Road Keighley West Yorkshire BD21 3ND Tel: 01535 610373 Fax: 01535 610801

Email: sales@vikingtapes.co.uk www.vikingtapes.co.uk

Product:

32 Micron PVC Solvent (Clear Film) Clear, White or Brown adhesive

Typical Applications:

- Manual Carton Sealing Tape
- Hand application
- Printable


Advantages & Benefits:

- Excellent adhesion
- Low Noise
- Tear by hand
- · Moisture resistant after application

Construction:

- Clear Poly Vinyl Chloride (PVC) film
- · Natural Rubber (Solvent) adhesive
- Unprinted & printed up to 4 colours*
- Widths available 9mm 144mm*
- Lengths available 33m 1056m*

CONSTRUCTION



*Lead times may vary depending on number of colours printed. Minimum order quantities apply.

Technical Data

Measure	<u>Unit</u>	Result & Tolerance
Film thickness	Microns	32 +/- 5%
Adhesive coat weight	Grams/square metre	18 +/- 5%
Total thickness	Microns	49 +/- 5%
Peel adhesion (Afera-5001)	Newtons/25mm	3 +/- 1
Elongation (Afera 5004)	%	<130
Tensile Strength (Afera 5004)	Newtons/cm	40 +/- 5%

Additional information

Tape performance is guaranteed for the first 6 months. Product must be stored at ambient temperature (Between 18c-23c), in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the batch identification number printed on the box. For optimum performance stock <u>should</u> be rotated and used within 12 months. The tapes have adhesive that are pressure sensitive so must be properly applied to ensure the best performance.

Physical and performance characteristics shown above are obtained following tests recommended by AFERA and PSTC. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

005VS1000TPDE