



VIKING

Industrial & Safety Supplies

Tel: 01535 610373
Email: sales@vikingtapes.co.uk

Unit 1, Coronation Business Park, Hard Ings Road, Keighley, West Yorkshire, BD21 3ND

VK1225 Double Sided Tape

CONSTRUCTION:

Backing: Non-woven Tissue Paper 14gms
Adhesive: Acrylic Solvent
Release liner: Silicone and PE Coating 125gms

TYPICAL PHYSICAL DATA:

Total Thickness(without liner): 160±5micron
180° Peeling Strength to Steel Plate: ≥1.8kg/25mm
Initial Tack (steel ball)14#: ≤100mm
Holding power: ≥24hours
80 °C Heat Resistance: ≥60minutes
180 °C Heat Resistance: ≥5minutes

PACKING:

Core I.D.: 3" (76mm±1)
Jumbo Roll: 1040/1020mm(or 1260/1240) x 1000m(any cut roll available upon request)
Packaging: Wrapped with corrugated cardboard,4 jumbos per wooden or plastic pallet

Remarks:

1. The above data are tested under lab condition; the last standard is subject to the last confirmation between the seller and the buyer.
2. Tolerance: Weight and Thickness: ±5%; Width: ±3mm;
Length: ±0.5%.
3. The products should be stored at room temperature and be kept away wet and/or heat source.
4. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
5. The users should take test before application so as to ensure suitability for their special purpose and technique.