



VK130 Double Sided Tape

DATA SHEET Double Sided PVC Tape 325micron

CONSTRUCTION:

Backing: Ivory PVC 100gms
Adhesive: Acrylic Solvent
Release liner: Gold Glassine 85gms

TYPICAL PHYSICAL DATA:

Total Thickness (without liner): 325 ± 10 micron
180° Peeling Strength to Steel Plate: ≥ 2.0 kg/25mm
Initial Tack (steel ball)14#: ≤ 55 mm
Holding power: ≥ 48 hours

PACKING:

Core I.D.: 3" (76mm ± 1)
Jumbo Roll: 1240mm x 1000m (any cut roll available upon request)
Packaging: Wrapped with corrugated cardboard, 4 jumbos per wooden or plastic pallet

Remarks:

1. The above data are tested under lab condition; the last standard is subject to the last confirmation between the seller and the buyer.
2. Tolerance: Weight and Thickness: $\pm 5\%$; Width: ± 3 mm;
Length: $\pm 0.5\%$.
3. The products should be stored at room temperature and be kept away wet and/or heat source.
4. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
5. The users should take test before application so as to ensure suitability for their special purpose and