



VK193 1mm Double Sided Foam Tape

CONSTRUCTION:

Backing: 3.0mm Polyethylene Foam (50kg/CBM)
Adhesive: Acrylic Solvent (stronger adhesive)
Release liner: PE liner or Glassine liner, or Silicone release poly-coating paper liner

TYPICAL PHYSICAL DATA:

Initial Tack: $\geq 29\text{N}/25.4\text{mm}$
180° Peeling Strength to Steel Plate : $\geq 21\text{N}/25.4\text{mm}$
Holding Power: $\geq 48\text{hours}$
Heat Resistance: $-20 \sim + 140 \text{ }^\circ\text{C}$

PACKING:

Core I.D.: 3" (76mm \pm 1)
Jumbo Roll: 1040mm x 100m
Packaging: Wrapped with corrugated cardboard, 4 jumbos per wooden or plastic pallet

Remarks:

1. The above data are tested under lab condition; the last standard is subject to the last confirmation between the seller and the buyer.
2. Tolerance: Weight and Thickness: $\pm 5\%$; Width: $\pm 3\text{mm}$;
Length: $\pm 0.5\%$.
3. The products should be stored at room temperature and be kept away wet and/or heat source.
4. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
5. The users should take test before application so as to ensure suitability for their special purpose and technique.