Unit 1, Coronation Business Park, Hard Ings Road, Keighley, West Yorkshire, BD21 3ND

## VK2732 - Double Sided Tape - Tissue

TECHNICAL DETAILS		TYPICAL VALUE	UNITS
Adhesive type: Pressure-sensitive hotmelt rubber/resin			
Thickness, adhesive + carrier Release liner thickness		0.080 0.055	mm mm
180 degree peel adhesion	Open side Closed side	800 800	N/m N/m
Polyester loop tack:	Open side Closed side	850 850	N/m N/m
Liner release		10	N/m
Tensile strength		1200	N/m
Elongation at break		10	%
Service temperature		-10 to +60	Deg. C.
Recommended application temperature		+5 to +60	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		Greater than 100	Hours
Shelf life		12	Months

Test Methods: BS 7116

This product is also available in fingerlift form. Standard formats 6/12, 9/15, 12/18, 18/24, 24/30. Other formats, including offset fingerlift available subject to minimum order quantities.

.THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY
ALL DATA IS BASED UPON AVERAGE VALUES THE PURCHASER SHALL BE RESPONSIBLE FOR
.DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES