



# VIKING

## Industrial & Safety Supplies

Tel: 01535 610373  
 Email: sales@vikingtapes.co.uk

Unit 1, Coronation Business Park, Hard Ings Road, Keighley, West Yorkshire, BD21 3ND

# VK3054 - Double Sided Tape - Polyester

### TECHNICAL DETAILS

### TYPICAL VALUE

### UNITS

Thickness, adhesive + carrier		0.070	mm
Release liner thickness		0.075	mm
180 degree peel adhesion:	Open side	750	N/m
	Closed side	750	N/m
Polyester loop tack:	Open side	850	N/m
	Closed side	850	N/m
Liner release		10	N/m
Tensile strength		4600	N/m
Elongation at break		12	%
Service temperature		-20 to +120	Deg. C.
Recommended application temperature		+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		20	Hours
Shelf life		12	Months

Test Methods: BS 7116

.THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY  
 ALL DATA IS BASED UPON AVERAGE VALUES THE PURCHASER SHALL BE RESPONSIBLE FOR  
 .DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES