Unit 1, Coronation Business Park, Hard Ings Road, Keighley, West Yorkshire, BD21 3ND

VK3902Toffee Tape

TECHNICAL DETAILS		TYPICAL VALUE	UNITS
Available Thicknesses		0.4 mm	
Release liner thickness		0.080	mm
180 degree peel adhesion:	Open side Closed side	>1000 N/A	N/m N/m
Polyester loop tack:	Open side Closed side	>1000 N/A	N/m N/m
Liner release		10	N/m
Tensile strength		N/A	N/m
Elongation at break		4	%
Service temperature, continuous		-10 to +60	Deg. C.
UV Resistance		Moderate	
Recommended application temperature		+10 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		>10	Hours
Shelf life		12	Months
Toot Mothada: BC 7116			

Test Methods: BS 7116

The values quoted above are based on limited test data and may be subject to change

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES

^{*}provides good bonding of LSE materials