



## VK196 High Bond Gel Tape

### CONSTRUCTION:

Adhesive: Acrylic Adhesive  
Liner: White Paper/Red Film  
Colour: Transparent

### TYPICAL PHYSICAL DATA:

Total Thickness:	1.0mm
Initial Tack (steel ball)14#:	≥20mm
180° Peeling Strength to Steel Plate:	≥25N/25mm
Holding Power:	≥72hours
80°C Heat Resistance:	≥120minutes
120°C Heat Resistance:	≥20minutes

### PACKING:

**Core I.D.:** 3" (76mm±1)  
**Jumbo Roll:** 840mm x 900m(any cut roll available upon request)  
**Packaging:** Wrapped with corrugated cardboard,4 jumbos per wooden or plastic pallet

### Remarks:

1. The above data are tested under lab condition; the last standard is subject to the last confirmation between the seller and the buyer.
2. Tolerance: Weight and Thickness: ±5%; Width: ±3mm;  
Length: ±0.5%.
3. The products should be stored at room temperature and be kept away wet and/or heat source.
4. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
5. The users should take test before application so as to ensure suitability for their special purpose and technique.