Unit 1, Coronation Business Park, Hard Ings Road, Keighley, West Yorkshire, BD21 3ND

VK330 Aluminium Foil Tape

Description

A 30 micron soft tempered bright aluminium foil. Coated with a pure Acrylic Adhesive, particularly suited to very low temperatures, on a honey glassine liner. Class 'O' approved

Typical Applications:

This product is recommended where a moisture barrier is required.

Technical Details	Typical Values Units
Adhesive Colour	Clear
Adhesive Type	Acrylic UV light resistance
Tape Thickness	0.06 mms (without liner)
Foil Thickness	0.030 mms
Peel Adhesion to Steel	920 N/M
Looptack to glass	640 N/M
Shear (Static) from glass	120 Hours @ 1kg
Fire propagation	Conforms to class 0 BS476 part 7 & 6 1987
Temperature Minimum Application	5° C
Service Range	-30° to 125° C
Shelf Life	12 months (PSMA Conditions)

Warranties

The above figures are average values and should not be regarded as maximum or minimum values for specification purposes.

The purchaser shall be responsible for determining the suitability of this product for his purposes. Goods which prove to be defective through faulty material or workmanship must be returned to us carriage paid. These will be replaced or credited. We shall not be liable for consequential damage incurred in the use of this material.