

monsta

WoodFix



What is Monsta WoodFix?

An all-natural repair compound and protective sealer for timber surfaces affected by wet and dry rot and insect attack.

The Monsta WoodFix has these features:

- Water based, free of solvents, non-toxic and non-flammable
- 100% natural, free of synthetic chemicals, biocides, insecticides and fungicides
- Restores timber strength
- Reverses timber rot deterioration process
- Protects against timber fungi and insects
- Fire retardant properties
- No shelf life
- Can be finished over with paints, stains and oils

Sizes: 1 & 4 Litre

Helpful info on how to use the Monsta WoodFix:

Surface Preparation

Ensure all loose damaged timber is removed. Surfaces to be treated are to be free of dust, grease, dirt, foreign matter and organic growth. Existing paints, stains and oils should be removed and sanded allowing Monsta WoodFix to penetrate into the timber to enable the natural protective and restoration process. Monsta WoodFix can be applied on timber that is slightly damp, but surfaces must be free of water and not contain excessive moisture. Optimum application is over a dried timber surface.

Coverage:

- Rot repairs - apply a minimum 2 coats at a total coverage of 1Lt/4-6m².
 - Protective coating over new and existing surfaces not affected by rot, minimum 1 coat at a total coverage of 1Lt/8m².
 - Fire retardant protective coating - apply 3 coats at a total coverage of 1Litre/3-4m².
 - Surface condition such as texture and porosity may affect coverage. Applying additional coats of WoodFix to surfaces will not have any negative effects on timber.
 - WoodFix can be applied to timber surfaces by brush, roller, spray unit or by dipping method
-

Where you can use Monsta WoodFix:

- Timber rot repairs and strengthening aged timber
- Protecting timber exposed to weather, moisture and humidity
- Fascias, timber eaves, window frames, joists, and doors
- Timber decking
- External timber structures and furniture

- Timber surfaces near children, animals, food and any exposed timber surfaces ensuring no emission or leaching of hazardous chemicals

Drying Times:

Re-Coat time2 hours

Application of paints stains or oils (if applicable).....min 72 hours

Note: Drying times will vary depending on porosity of timber, type of timber and surrounding environment.

Tips to use the Monsta WoodFix:

- Before commencing, the product should be tested on a typical area or surface to check appearance and application.
- Before using any brushes or rollers, ensure they are dry and do not contain residues from paints, sealers or varnishes.
- Application tools must be free of any other coatings or residues as these materials will negatively affect Monsta WoodFix's performance.
- For optimum natural eco-friendly finish, linseed oil based paints and stains are recommended.
- WoodFix is natural but very alkaline so use gloves and protective glasses when applying

Clean up - Clean up with water while wet. Once product is dried on rollers or brushes, soak in soapy water overnight then rinse thoroughly

Important information to take note of:

- Monsta WoodFix will not enable non-structural supporting timber to become structurally supporting.
- Optimum performance is the restoration of the original strength of the timber surface. Will not provide original strength of timber if timber mass has been lost from the surface.
- Do not apply to exterior surfaces when rain is imminent, best applied when the area will be free of rain for a minimum 5 days. Best results on external timber - protect from rain and sitting water for 3 weeks
- Do not apply when surface temperature is below 5°C and above 35°C
- For exposed timber surfaces, the timber will appear stained for the first 21 days before returning to a more natural appearance over the course of 1-2 months. WoodFix treats timber naturally, hence different woods will react differently
- For treating timber rot, there will be an ongoing change of the timber appearance in the first month while the natural restoration process takes place
- Mild temporary discolouration may occur on some timbers, this will only be temporary while the Monsta WoodFix repair process takes place.
- Porous timber surfaces will appear with a slight "pine coloured" seal effect.
- Timber will look deeper in colour after the application.
- Ensure any spillage or wet residues onto metals, glazed surfaces or plastics are immediately removed with a damp cloth/wipe to prevent staining.

Axis Manufacture Pty Ltd
ABN: 41 094 789 929
www.Monstashop.com

30-32 Park Avenue
Woodville North 5012, South Australia
Phone (08) 8124 7360