

Technical Data Sheet: BeRoll Dynamic Revision: January 2020

Dynamic

Dynamic is our rubber roll for those who are on a tighter budget. Reliable and cost effective, meet **Dynamic SERIES**, one of our best selling products.



COMPOSITION

Fine Recycled SBR granule and MDI polyurethane boding agent.

SPECIFICATIONS

Usage	Indoor / Outdoor
Size	1000 x 120 cm
Thickness / Weight	8 mm / 7,70 kg/m²
Color	
Surface	Porous, soft and smooth
Density	950-970 kgs/m ³
Tolerance	5%



APPLICATION AREAS

Dynamic Rolls have wide application area: protective cover for other flooring (exhibitions, etc.), sub-base for multipurpose sport area & tennis court, accoustic isolation material for buildings, gym flooring, etc.

PROPERTIES

Fire Resistance	Class E (DIN EN 13501)
Chemical Resistance	Conditionally resistant to acids and bases
Cold Fracture Resistance	24 hours / -20° C, no fracture
Cold Cracking Resistance	5 hours / -15° C, no crack

The product data sheet is not subject to any change service

All information is without guarantee.

You can find the latest version of this document on the relevant product page at www.cannonsuk.com

Cannons Flooring Limited Unit 4/5 Fysons Farm, Thetford Road, Diss, Norfolk, IP22 2HQ - United Kingdom 01379687768 - sales@cannonsuk.com



