

ABUC-LED

Construction:

- Steel Pan
- Steel spun trim ring
- Diffuser is white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**
- Replaceable LED Engine

Notes:

- Keyhole slots for standard J-box
- Brushed Nickel finish (standard)
- Cast uplight accent
- Wall or ceiling mount
- Fastnerless appearance
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



ABUC-14-LED

Height - 5 5/8"
Diameter - 14"



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: ABUC-14-LED-U-20W-4-P9-WSA

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
ABUC-14-LED		U 120 - 277	13w 1,484 lm (Dim) 20w 2,325 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD)	2 3000K 4 4000K Optional 3 3500K	P9 Brushed Nickel Optional (See Price List) B1 Satin Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i> OCCHFA Integrated Sensors <i>See Sensor Resource Sheet</i> Battery Backup Options <i>(On Board Driver Engine only)</i> BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

