

BACV-LED

Construction:

- Steel chassis
- Diffuser is an extruded lens featuring an artistic die-cut design producing crystalizing effects between prismatic clear and white acrylic.
- End caps are acrylic and are available in standard White and metallic silver.

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Mounts to standard 2x4 J-Box with slotted anchor holes
- ADA compliant
- Custom designed faces and caps are available.
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

BACV-24

Height - 4 ¾"
 Depth - 4"
 Length - 25 ½"

Type:	
Job Name:	



Shown with -MS Metallic Silver End Caps



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: BACV-24-LED-U-26W-2-MS-DRA

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
BACV-24-LED		U 120 - 277	14w LED / 2249lm 26w LED / 4629lm	2 3000K 4 4000K Optional 3 3500K	SW Solid White End-Caps MS Metallic Silver End-Caps Optional End-Caps (see Price List) Consult Factory	DRA Dancing Reeds Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) DIMLD LED Phase dimming driver (TRIAC / ELV) Dimming to 10% (Optional) Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

