

BLSC-LED

Construction:

- Steel pan and fins
- Diffuser is white frosted acrylic lens designed for LED light source

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring
- Optional occupancy sensor
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



BLSC-14-LED

Width - 14"
 Height - 4 3/4"
 w/ext ring - 6 1/2"



ORDERING INFORMATION

Example: BLSC-14-LED-U-20W-4-W2-WFA

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
BLSC-14-LED		U 120 - 277	13w 1,484 lm (Dim) 20w 2,325 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page 42 Aluminum Pan 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Battery Backup Options (Requires 1 3/4" extension ring) (On Board Driver Engine only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

