

BPRH-LED

Construction:

- Steel top, bottom and rings
- Cylinder is .125" thick white smooth acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Mounts standard "J-Box", hardware included
- Standard is 3' of chain with 6' of cord
- Optional single stem and 45-degree swivel
- Bottom of fixture is open; optional clear bottom lens or solid bottom cover (no down light)
- UL and CUL listed **DAMP** location
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Shown with solid bottom cover



BPRH-12

Height - 12"

Width - 7 1/4"

OAH - 36"

BPRH-16

Height - 16"

Width - 8 1/2"

OAH - 36"

WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: BPRH-16-LED-U-42-Z3-WSA-SSB

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
BPRH-12-LED		U 120 - 277	36w LED / 4000lm (111 lm per watt)	2 3000K 4 4000K	B1 Satin Black Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
BPRH-16-LED			42w LED / 4900lm (117 lm per watt)	Optional 3 3500	Optional (See Price List) W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige		CBL Clear Bottom Lens SSB Solid Bottom Cover (Optional Suspension) (See Price List) CHN - 3' of chain and 6' cord (STD) 1S45 - Single 45° Swivel Stem WSJ - White "SJ" Cord BSJ - Black "SJ" Cord



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

