

BPSH-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth or textured polycarbonate.
- Optional amber, beige or opal alabaster acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Mounts standard "J-Box", hardware included
- Standard is 3' of chain with 6' of cord
- Optional stem and swivel mounting – consult Factory
- Bottom of fixture is open; optional clear bottom lens or solid bottom cover (no down light)
- UL and CUL listed **DAMP** location
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

BPSH-12

Height - 12"
Width - 7 1/2"

BPSH-16

Height - 16"
Width - 8 1/2"

BPSH-22

Height - 22"
Width - 10"



ORDERING INFORMATION

Example: BPSH-12-LED-U-36W-3-Z3-WSP-CBL

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
BPSH-12-LED		U 120 - 277	36w LED / 4000lm (111 lm per watt)	2 3000K 3 3500K 4 4000K	B1 Satin Black Z1 Satin Bronze Z3 Text Bronze	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
BPSH-16-LED			42w LED / 4900lm (117 lm per watt)		Optional Finishes (see Price List) W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSP White Smooth polycarbonate	CBL Clear Bottom Lens SSB Solid Bottom Cover
BPSH-22-LED			144w LED / 16,00lm (111 lm per watt)			Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	SSV Stem with Swivel Canopy



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

