

BRLW-LED

Construction:

- Steel housing and chassis
- Diffuser is .060" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Open top and bottom allows for up/down light
- ADA compliant
- Optional battery backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



BRLW-11

Height - 11"
Width - 7 1/4"
Depth - 4"



WALL
CEILING
PENDANT
OUTDOOR

ORDERING INFORMATION

Example: BRLW-11-LED-U-13W-3-B1-WTP

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
BRLW-11-LED		U 120 - 277	13w 1,484 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional Finishes (see Price List) W1 Yolk T1 Silver/Gray T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	WTP White Textured Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i> Battery Backup Options <i>(On Board Driver Engine only)</i> BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

