

BWXW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional Photocell (21)
- Optional battery backup
- J-Box with knockouts for surface mount conduit - increases depth to 4"
- ADA compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

BWXW-9

Height - 8 1/2"
Width - 4 1/2"
Depth - 3 1/2"

BWXW-11

Height - 11"
Width - 7"
Depth - 4"



ORDERING INFORMATION

Example: **BWXW-9-LED-U-10W-3-Z1-WTP**

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
BWXW-9-LED		U 120 - 277	10w LED / 1050lm (131 lm per watt) 14w LED / 1600lm (131 lm per watt)	2 3000K 4 4000K Optional 3 3500K 5 5000K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (See Price List)	WTP White Textured Polycarbonate Optional Lens Material (See Price List) CTP Clear Textured Polycarbonate	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 21 Photocell - See Notes -01 120 volt -02 277 volt 39 J-Box with Knockouts 42 All Aluminum Construction Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes
BWXW-11-LED			10w LED / 1050lm (131 lm per watt) 14w LED / 1600lm (131 lm per watt)		W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass		



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

