

CALC-LED

Construction:

- Steel housing and steel chassis
- Diffuser is .080" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Optional battery backup - increases depth by 1 1/2"
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

CALC-12

Height - 4"
Width - 11 1/2"

CALC-16

Height - 4"
Width - 15 1/2"



ORDERING INFORMATION

Example: CALC-12-LED-U-13W-4-B1-WTP

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
CALC-12-LED		U 120 - 277	13w LED / 1,484 lumens 20w LED / 2,325 lumens	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List)	WTP White Textured Polycarbonate WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
CALC-16-LED		1 120 Volt	20w LED / 2,325 lumens (116 lm per watt) Socket Base: (Lamp by Others) E26 Medium Base (NL) * Battery Backup not available		W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> (Only available in 20 watt) Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

