

CAMC-LED

Construction:

- Steel housing and steel chassis
- Diffuser is .080" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Optional Dimming driver
- UL and CUL listed **DAMP** location
- LED Array
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

CAMC-12

Height - 5"
Width - 11 1/2"

CAMC-16

Height - 7"
Width - 15 1/2"



ORDERING INFORMATION

Example: CAMC-12-LED-U-13W-4-B1-WTP-DIM

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
CAMC-12-LED		U 120 - 277	13w LED / 1,484 lumens 20w LED / 2,325 lumens E26 Medium Base (NL)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List)	WTP White Textured Polycarbonate WSP White Smooth Polycarbonate Optional Lens Material (see Price List)	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet (Only available in 20 watt)
CAMC-16-LED		1 120 Volt	36w LED / 4,000 lumens E26 Medium Base (NL) Socket Base: (Lamp by Others) E26 Medium Base (NL) * Battery Backup not available		W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

