CHSC-LED

WALL | CEILING | PENDANT | OUTDOOR

Construction:
- Steel housing and chassis
- Clear prismatic polycarbonate lens

Light Source:
- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:
- Keyhole slots for standard "J-Box" mounting
- Optional photocell - option 21 (specify voltage)
- Optional battery backup
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Integral Power Supply
  - 5-Year Warranty on LED Components

Type:	
Job Name:	

CHSC-11
Height - 6 ½"
Width - 10 ½"
Depth - 10 ½"

ORDERING INFORMATION

Example: CHSC-11-LED-U-28W-3-Z1-CPP

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
CHSC-11-LED		**U** 120 - 277 **1** 120 volt	**14w** LED / 1600lm (114 lm per watt) **28w** LED / 3200lm (114 lm per watt) **Socket Base: (Lamp by Others)** **E26** Medium Base (NL) **E39** Moqul Base (NL) * Battery Backup not available	**2** 3000K **3** 3500K **4** 4000K	**B1** Satin Black **Z1** Satin Bronze **Z3** Text Bronze **Optional** *(See Price List)* **W1** Yolk **W2** Gloss White **W3** Text White **B2** Text Black **T4** Shimmer Gray **M13** Anod Silver **T6** Pewter **W13** Pearl Beige	**CPP** Clear Prismatic Polycarbonate **Optional Lens Material** *(See Price List)* **WSP** White Smooth Polycarbonate	**DIM** LED dimming driver (0 - 10v) Dimming to 10% (**Included**) **21** Photocell - Spedify voltage 01 - 120 volt 02 - 277 volt **OCCHFA** Concealed Occupancy Sensor *See Sensor Resource Sheet* **Battery Backup Options** **BB10** 10 Watts (1170lm) for 90-Minutes

28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286• fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com