

CLPC-LED

Construction:

- Diffuser is white smooth acrylic
- Optional Polycarbonate diffuser (WSP) or high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring (14" & 19" only)
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

CLPC-11-LED
Height - 3"
Diameter - 11"

CLPC-14-LED
Height - 3 1/2"
w/ext ring - 5 1/4"
Diameter - 14"

CLPC-19-LED
Height - 3 3/8"
w/ext ring - 5 1/4"
Diameter - 19"



ORDERING INFORMATION

Example: CLPC-14-LED-U-20W-4-W2-WSA-DIM

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
CLPC-11-LED		U 120 - 277	13w 1,484 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD)	2 3000K 4 4000K Optional 3 3500K	W2 Gloss White	WSA White Smooth Acrylic Optional Lens Material (see Price List) WSP White Smooth Polycarbonate WSAHE White Smooth Acrylic High Efficiency	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i> 42 Aluminum Pan (11" & 14" only) OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Battery Backup Options <i>(Requires 1 3/4" extension ring)</i> <i>(On Board Driver Engine only)</i> CCLC-14 and 19 only BB10 10 Watts (1170lm) for 90-Minutes
CLPC-14-LED			20w 2,325 lm (Dim) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)				
CLPC-19-LED			36w 4,000 lm (Dim)				



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

