

Construction:

- Steel pan
- Diffuser is white smooth acrylic
- Optional polycarbonate diffuser

Lamps:

- Lamps **INCLUDED**

Notes:

- Keyhole slots for standard J-Box installation
- Dimming ballast may be limited with some lamps
- Optional aluminum pan (11" and 14" only)
- Optional Battery backup - 14" and 19" only (increases depth by 1 3/4")
- UL and CUL listed **DAMP** location

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

CMLC-11	CMLC-14	CMLC-19
Height - 4 1/4"	Height - 4 1/2"	Height - 4 1/4"
Diameter - 11"	Diameter - 14"	Diameter - 19"



ORDERING INFORMATION

Example: CMLC-14-A-2Q26-4-W2-WSA-42

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
CMLC-11		A 120v NPF (Elec) U 277v HPF (Elec)	2Q13 (2) 13w Elec 2Q18 (2) 18w Elec 1Q26 (1) 26w Elec	2 2700K 3 3500K 4 4100K	W2 Gloss White	WSA White Smooth Acrylic	(Dimming option - See Notes) DIM10 - Mark 10 Dimming Ballast DIM7 - Mark 7 Dimming Ballast 01 120v 02 277v 42 Aluminum Pan (11" & 14" only) (BB option - 14" & 19" size only) BB - Battery Backup 01 120v 02 277v 06 650 Lumen (nominal) 12 1250 Lumen (nominal)
CMLC-14			2Q13 (2) 13w Elec 3Q13 (3) 13w Elec 2Q18 (2) 18w Elec 2Q26 (2) 26w Elec 1T32 (1) 32w Elec 1T42 (1) 42w Elec				
CMLC-19			3Q26 (3) 26w Elec 2T32 (2) 32w Elec 2T42 (2) 42w Elec				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

