

Construction:

- Die cast aluminum housing
- Clear prismatic polycarbonate lens

Lamps:

- Lamps **INCLUDED**

Notes:

- Keyhole slots for standard "J-Box" mounting
- Pulse start magnetic ballast and lamp with (MH)
- Photocell - option 21 (field installable by others)
- Battery backup with two 2 Q26 or 2T32 lamps only
- CSA listed **WET** location

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

CXLC-12

Height - 8 3/4"
Width - 12 1/2"
Depth - 12 1/2"

ORDERING INFORMATION

Example: CXLC-12-7-1M150 -T-Z99-CPP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
CXLC-12		A 120v NPF (Elec) U 277v HPF (Elec) 7 Quad-tap (Mag)	2Q26 (2) 26w Elec 2T32 (2) 32w Elec 2T42 (2) 42w Elec 1M70 (1) 70w MH Mag 1M100 100w MH Mag 1M150 150w MH Mag	2 2700K 3 3500K 4 4100K T (MH)	Z99 Bronze	CPP Clear Prismatic Polycarbonate Optional Lens Material <i>(See Price List)</i> WSP White Smooth Polycarbonate	21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt (BB option - See Notes) BB - Battery Backup CBB - Cold Weather BB 01 120v 02 277v 06 650 Lumen (nominal) 12 1250 Lumen (nominal)



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

