

CXLC-LED

Construction:

- Die cast aluminum housing
- Clear prismatic polycarbonate lens

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Keyhole slots for standard "J-Box" mounting
- Optional photocell (21)
- Optional battery backup
- CSA listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Integral Power Supply
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

CXLC-12

Height - 8 ¾"
Width - 12 ½"
Depth - 12 ½"



ORDERING INFORMATION

Example: CXLC-12-LED-U-36W-3-Z99-CPP

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
CXLC-12-LED		U 120 - 277 1 120 volt	36w LED / 4000lm (117 lm per watt) Socket Base: (Lamp by Others) E26 Medium Base (NL) E39 Moquil Base (NL) * Battery Backup not available	2 3000K 3 3500K 4 4000K	Z99 Bronze	CPP Clear Prismatic Polycarbonate Optional Lens Material <i>(See Price List)</i> WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

