

ETOV-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth acrylic
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Perforated front panel (PP) reduces front lighting
- Solid top (ST) eliminates up light
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



ETOV-18	ETOV-24	ETOV-36
Height - 4½"	Height - 4½"	Height - 4½"
Depth - 3¼"	Depth - 3¼"	Depth - 3¼"
Length - 18"	Length - 24"	Length - 36"



WALL
CEILING
PENDANT
OUTDOOR

ORDERING INFORMATION

Example: ETOV-24-LED-U-21W-3-Z3-WSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
ETOV-18-LED		U 120 - 277	14w LED / 1600lm (114 lm per watt)	2 3000K 4 4000K	B1 Satin Black Z1 Satin Bronze Z3 Text Bronze W2 Gloss White	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
ETOV-24-LED			21w LED / 2450lm (117 lm per watt)	Optional 3 3500K	Optional Finish (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	PP Perforated Front Panel ST Solid Top (No Up Light)
ETOV-36-LED			32w LED / 3675lm (117 lm per watt)				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

