

FLPA-LED

Construction:

- Steel housing and chassis
- Diffuser is Clear Smooth Acrylic or optional White Frosted Acrylic

Light Source:

- LED
- Dimming (Triac) to 10% **Included**

Notes:

- ½" NPT knuckle mounts to junction box or ground fitter
- Photocell (21)
- Optional Grid Louver (GL) reduces side glare
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



FLPA-5

Height - 4 ½"

Width - 8 ½"

Depth - 2 ½"



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: FLPA-5-LED-U-14W-2-B1-CSA-2102

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
FLPA-5-LED		U 120, 208, 240, 277	10w LED / 1175lm (117 lm per watt) 14w LED / 1600lm (114 lm per watt)	2 3000K 3 3500K 4 4000K 5 5000K	B1 Satin Black Optional (See Price List) W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Z1 Satin Bronze Z3 Text Bronze	CSA Clear Smooth Acrylic Optional (See Price List) WFA White Frosted Acrylic	DIMLD Line Dim (120v only) 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt 84 Ground Fitter GL Grid Louver



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

