

# JPBW-LED

## Construction:

- Steel Housing
- Diffuser is white textured polycarbonate

## Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

## Notes:

- Integral mounting plate for standard "J-Box"
- Mounting orientation is downward
- Optional photocell attaches to wall mounting bracket, specify 120v or 277v
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

### JPBW-13

Height - 13"  
Width - 11"  
Depth - 12.2"



## ORDERING INFORMATION

Example: JPBW-LED-13-U-11W-3-Z3-WTP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
<b>JPBW-13-LED</b>		<b>U</b> 120 - 277	<b>11 w</b> LED / 1100lm (100 lm per watt)	<b>2</b> 3000K <b>4</b> 4000K  <b>Optional</b> <b>3</b> 3500K	<b>B1</b> Satin Black <b>W2</b> Gloss White <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze  <b>Optional Finishes</b> (See Price List) <b>W1</b> Yolk <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige	<b>WTP</b> White Textured Polycarbonate	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% <b>(Included)</b>  <b>Z1</b> Photocell - Specify voltage 01 - 120 volt 02 - 277 volt



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

