

Construction:

- Steel housing hung from a decorative rigid frame
- Diffuser is .080" thick white textured or optional white smooth polycarbonate.
- Optional alabaster lenses are .080" thick acrylic

Lamps:

- Lamps **INCLUDED**

Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom heights available
- Chain link swivel standard
- Optional dimming ballast available with select lamping
- Standard bottom lens is white smooth polycarbonate; optional clear acrylic or solid cover
- UL and CUL listed DAMP location

Type:	
Job Name:	



Overall Fixture

Diameter - 60"
OAH - 60"

Individual Fixtures

Height - 15 1/2"
Width - 11 1/2"
Depth - 11 1/2"

WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: JPTH-416-U-4T32-4-Z3-WSA-WBL

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Bottom Lens
JPTH-416		A 120v NPF (Elec) U 277v HPF (Elec)	4Q26 (4) 26w Elec One lamp per fixture 8Q26 (8) 26w Elec Two lamps per fixture 4T32 (4) 32w Elec One lamp per fixture 4T42 (4) 42w Elec One lamp per fixture	2 2700K 3 3500K 4 4100K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (See Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	WBL White Bottom Lens (Standard) CBL Clear Bottom Lens (Optional) SBC Solid Bottom Cover (Optional) (Dimming option - See Notes) DIM10 - Mark 10 Dimming Ballast 01 120v 02 277v

