

LCSW-LED

Construction:

- Aluminum chassis; accent bar is aluminum
- Diffuser is .10" thick white smooth acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup – hardware included
- Open top and bottom
- Horizontal or vertical mounting
- ADA compliant
- Optional Battery Backup with LCSW-16 & LCSW-26
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL
 CEILING
 PENDANT
 OUTDOOR

LCSW-12

Height - 12"
 Width - 9 1/4"
 Depth - 4"

LCSW-16

Height - 16"
 Width - 9 1/4"
 Depth - 4"

LCSW-26

Height - 26"
 Width - 9 1/4"
 Depth - 4"



ORDERING INFORMATION

Example: LCSW-16-LED-U-14W-3-T6-WSA-BLA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Accent / Options
LCSW-12-LED		U 120 - 277	14w LED / 1600lm (114 lm per watt)	2 3000K 4 4000K	B1 Satin Black T6 Pewter Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	BLA Blue Center Lens ABA Amber Center Lens GNA Green Center Lens AHA Amber Honey Center Lens WSA White Center Lens
LCSW-16-LED			14w LED / 1600lm (114 lm per watt)	Optional 3 3500K	Optional Finishes (see Price List) T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass		(Dimming option - See Notes) DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
LCSW-26-LED			21w LED / 2450lm (117 lm per watt)				Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

