

Construction:


- Steel chassis
- Diffuser is a white smooth acrylic lens with a top and bottom lens.
- Lens is offset from wall 1/2"

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



LTCW-12-LED

Dim 'A' - 12"
 Dim 'B' - 7 3/4"
 Dim 'C' - 4"
 Dim 'MC' - 6"

Type:	
Job Name:	



WALL
 CEILING
 PENDANT
 OUTDOOR

ORDERING INFORMATION

Example: LTCW-16-LED-U-13W-3-M13-WSA

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Accent / Options
LTCW-12-LED		U 120 - 277	13w 1,484 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black T6 Pewter Z1 Satin Bronze Z3 Text Bronze Optional Finishes (see Price List) T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i>

