

MACC-LED

Construction:

- Steel housing and chassis
- Diffuser is white smooth polycarbonate.
- Optional alabaster lenses are .080" thick acrylic

Lamps:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup – hardware included
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

MACC-12

Height - 6"

Width - 11 1/2"

Length - 7 1/2"



ORDERING INFORMATION

Example: MACC-12-LED-12-U-13W-4-Z3-WTP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
MACC-12-LED		U 120 - 277	13w LED / 1,484 lumens (114 lm per watt)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	WSP White Smooth Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

