

MRRW-916

Construction:

- Steel housing and chassis
- Diffuser is .10 extruded white acrylic
- Top and bottom white acrylic lens - standard
- Accent rings are steel tubing

Lamps:

- Lamps **INCLUDED**

Notes:

- Integral mounting plate; keyhole slots left and right
- Top and bottom white acrylic lens - standard
- Dimming ballast may be limited with some lamps
- Photocell (21) increases fixture depth 1 1/2"
- Photocell (21)- specify voltage 120v or 277v
- Aluminum lens cover (ALC) eliminates up/down light
- Battery backup may be limited or unavailable with some lamping
- UL and CUL listed **WET** location

Height - 16"
 Width - 9"
 Depth - 5 1/2"
 MC - 8"

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: MRRW-916-P-U-1M39-T-Z3-WSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
MRRW-916	P X	A 120v NPF (Elec) U 277v HPF (Elec)	2Q13 (2) Q13w 2Q26 (2) Q26w 2T32 (2) T32w 1T42 (1) T42w 1B24 (1) 24w Biax 2B24 (2) 24w Biax 1M39 (1) 39w MH Elec	2 2700K 3 3500K 4 4100K T (MH)	B1 Satin Black Z1 Satin Bronze Z3 Text Bronze Optional (See Price List) W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	(Dimming option - See Notes) DIM10 - Mark 10 Dimming Ballast DIM7 - Mark 7 Dimming Ballast 01 120v 02 277v 21 Photocell - <i>Specify voltage</i> 01 120v 02 277v ALC Aluminum Lens Cover- <i>See Notes</i> (BB option - See Notes) BB - Battery Backup CBB - Cold Weather BB 01 120v 02 277v 05 500 Lumen (nominal) 06 650 Lumen (nominal) 12 1250 Lumen (nominal)



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

