

### Construction:

- Steel housing
- Diffuser is white smooth acrylic

### Light Source:

- LED
- Dimming to 10% **Included**

### Notes:

- Canopy mounts to standard J-Box – hardware included
- Optional stem heights available
- Dimming ballast may be limited with some lamps
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

#### NAPC-13

Height - 13 3/8"  
Diameter - 12 7/8"

#### NAPC-17

Height - 13 3/8"  
Diameter - 17"

#### NAPC-19

Height - 13 3/8"  
Diameter - 20 5/8"



## ORDERING INFORMATION

**Example: NAPC-17-LED-U-20W-4-W2-WSA**

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
<b>NAPC-13-LED</b>		<b>U</b> 120 - 277	<b>13w</b> 1,484 lm (Dim)	<b>2</b> 3000K <b>4</b> 4000K	<b>W2</b> Gloss White	<b>WSA</b> White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i>
<b>NAPC-17-LED</b>			<b>20w</b> 2,325 lm (Dim) <b>15ACw</b> 1,724 lm (DimLD) <b>23ACw</b> 2,540 lm (DimLD)	<b>Optional</b> <b>3</b> 3500K	<b>Optional</b> (see Price List) <b>P9</b> Brushed Nickel		<b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i>
<b>NAPC-19-LED</b>			<b>36w</b> 4,000 lm (Dim)				<b>Battery Backup Options</b> <i>(Requires 1 3/4" extension ring)</i> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes

