

NASW-LED

Construction:


- Steel housing
- Diffuser is .060" thick white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to Standard J-box – hardware included
- Optional battery backup - Requires 1 3/4" extension ring
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



Type:	
Job Name:	



Battery Backup option



NASC-13

DIM 'A' - 12 7/8"
DIM 'B' - 3"

NASC-17

DIM 'A' - 17"
DIM 'B' - 3 5/8"

NASC-19

DIM 'A' - 20 5/8"
DIM 'B' - 4"

WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: NASW-17-LED-U-20W-4-W2-WSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
NASW-13-LED		U 120 - 277	13w 1,484 lm (Dim)	2 3000K 4 4000K	W2 Gloss White	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i>
NASW-17-LED			20w 2,325 lm (Dim) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)	Optional 3 3500K	Optional (see Price List) P9 Brushed Nickel		DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i>
NASW-19-LED			36w 4,000 lm (Dim)				Battery Backup Options <i>(Requires 1 3/4" extension ring)</i> BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

