

PARK BOLLARDS-LED

Construction:

- Extruded aluminum housing with flush mounting base
- Interior cast aluminum louvers (PFLB/POLB/PSLB)
- Clear prismatic borosilicate glass refractor (PFGB/POGB/PSGB)
- Clear polycarbonate lens (all models)

Light Source:

- LED

Notes:

- Vandal-resistant screws
- Type III or Type V refractor (PFGB/POGB/PSLB)
- Mounting kit with (3) 4" anchor bolts included
- Mounting kit may ship separately for pre-installation
- Custom heights available – consult Factory
- CSA listed **WET** location
- LED Components
 - CRI > 80
 - 5-Year Warranty on LED Components

PFGB/PFLB	PSGB/PSLB
POGB/POLB	Height - 43 ³ / ₈ "
Height - 43 ³ / ₈ "	Width - 7"
Diameter - 7"	Depth - 7"
Base - 7"	Base - 7"

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: POGB-43-LED-1-E26-NL-B99-CSP-T3

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
PFGB-43-LED PFLB-43-LED POGB-43-LED POLB-43-LED PSGB-43-LED PSLB-43-LED		U 120/277 A 120 volt	Integrated LED Source: 12w LED / 1220lm (101 lm per watt) 20w LED / 2360lm (118 lm per watt) Socket Base: (Lamp by Others) 1E26 Medium Base (NL)	2 3000K 4 4000K Optional 3 3500K	B99 Black	CSP Clear Smooth Polycarbonate (Refractor Type) T3 Type III Refractor T5 Type V Refractor (PFGB/POGB/PSGB Only)	



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

