

PCLH-LED

Construction:

- Steel pan and rings
- Diffuser is white smooth acrylic
- Optional Polycarbonate diffuser (WSP) or high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Canopy mounts to standard J-Box
- Custom stem heights available
- No uplight
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



3R Option

WALL

CEILING

PENDANT

OUTDOOR

PCLH-15
Height - 3 ¼"
Diameter - 15
Overall Height - 24"

PCLH-21
Height - 3 ¼"
Diameter - 21 ¼"
Overall Height - 24"



ORDERING INFORMATION

Example: PCLH-21-LED-U-36W-4-Z1-WSA

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
PCLH-15-2R-LED PCLH-15-3R-LED		U 120 - 277	20w LED / 2,325 lumens	2 3000K 4 4000K	T6 Pewter W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List)	WSA White Smooth Acrylic Optional Lens Material (see Price List) WSP White Smooth Polycarbonate WSAHE White Smooth Acrylic High Efficiency	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i>
PCLH-21-2R-LED PCLH-21-3R-LED			36w LED / 4,000 lumens	3 3500	W1 Yolk W3 Text White B1 Satin Black B2 Text Black T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige		



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

