

PFBC-LED

Construction:


- Steel pan
- Bowl is white smooth acrylic
- Optional alabaster bowls are smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box installation
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



PFBC-17

Height - 4 1/2"
Width - 17"

Type:	
Job Name:	



Shown with Deco Trim



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: PFBC-17-LED-U-20W-3-Z1-WSA-DT

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
PFBC-17-LED		U 120 - 277	13w 1,484 lm (Dim) 20w 2,325 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)	2 3000K 3 3500K 4 4000K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i> DT Deco Trim OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i>



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

