

PLSH-LED

Construction:

- Steel pan
- Diffuser is frosted smooth glass
- Optional white smooth acrylic bowl


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to standard J-Box
- Custom mounting heights available
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

	PLSH-17	PLSH-21
A	5"	7"
B	16 1/2"	16 1/2"
OAH	12 1/2"	12 1/2"



Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: PLSH-21-LED-U-23ACw-4-T4-FSG

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
PLSH-17-LED		U 120 - 277	13w 1,484 lm (Dim) 20w 2,325 lm (Dim) 27w 3,000 lm (Dim) 36w 4,000 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)	2 3000K 4 4000K Optional 3 3500	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	FSG Frosted Smooth Glass Optional Lens Material (see Price List)	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i> OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes
PLSH-21-LED			20w 2,325 lm (Dim) 36w 4,000 lm (Dim) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

