

PLVC-LED

Construction:

- Steel pan
- Diffuser is frosted smooth glass

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box installation
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

PLVC-17
Height - 5 1/4"
Diameter 16 1/2"

PLVC-21
Height - 7"
Diameter 20 3/4"



ORDERING INFORMATION

Example: PLVC-21-LED-U-36W-4-T6-FSG

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
PLVC-17-LED		U 120 - 277	13w 1,484 lm (Dim) 20w 2,325 lm (Dim) 27w 3,000 lm (Dim) 36w 4,000 lm (Dim) 10ACw 1,065 lm (DimLD) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)	2 3000K 4 4000K Optional 3 3500	W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B1 Satin Black B2 Text Black T4 Shimmer Gray T6 Pewter M13 Anod Silver W13 Pearl Beige M16 Antique Brass P7 Brushed Steel P9 Brushed Nickel	FSG Frosted Smooth Glass	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i> OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes
PLVC-21-LED			20w 2,325 lm (Dim) 36w 4,000 lm (Dim) 15ACw 1,724 lm (DimLD) 23ACw 2,540 lm (DimLD)				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

