

# PMLC-LED

## Construction:

- Steel housing and chassis
- Elliptical white smooth acrylic bowl is standard
- Optional alabaster bowl

## Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

## Notes:

- Chassis mounts to standard J-Box
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



**PMLC-24-LED**  
Height - 7"  
Width - 24"

**PMLC-36-LED**  
Height - 10"  
Width - 36"



WALL

CEILING

PENDANT

OUTDOOR

## ORDERING INFORMATION

Example: PMLC-36-LED-U-189W-3-Z1-WSA

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
<b>PMLC-24-LED</b>		U 120 /277v	<b>36w</b> LED / 4,000 lumens <b>63w</b> LED / 7,350 lumens <b>84w</b> LED / 9,800 lumens <b>95w</b> LED / 11,025 lumens	<b>2</b> 3000K <b>4</b> 4000K  Optional <b>3</b> 3500	<b>B1</b> Satin Black <b>W2</b> Gloss White <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze  Optional (see Price List) <b>W1</b> Yolk <b>W3</b> Text White <b>B2</b> Text Black <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige	<b>WSA</b> WhiteSmooth Acrylic  <b>Optional Lens Material</b> (see Price List)  <b>AHA</b> Amber Honey Alabaster <b>BAA</b> Beige Alabaster <b>OAA</b> Opal Alabaster	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% <b>(Included)</b>         <b>Battery Backup Options</b> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
<b>PMLC-36-LED</b>			<b>36w</b> LED / 4,000 lumens <b>60w</b> LED / 7380 lumens <b>63w</b> LED / 7,350 lumens <b>84w</b> LED / 9,800 lumens <b>126w</b> LED / 14,700 lumens <b>189w</b> LED /22,050 lumens				



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

