

# PNBC-LED

## Construction:

- Steel pan
- Diffuser is frosted smooth glass

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots for standard J-Box installation
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

**PNBC-17**  
Height - 5 ¾"  
Diameter 16 ½"

**PNBC-21**  
Height - 7 ¼"  
Diameter 20 ¾"



## ORDERING INFORMATION

**Example: PNBC-21-LED-U-42W-4-T6-FSG**

Model	Cage	Voltage	Lumens/Source	Kelvin	Finish	Diffuser	Options
<b>PNBC-17-LED</b>		U 120 - 277	<b>13w</b> 1,484 lm (Dim) <b>20w</b> 2,325 lm (Dim) <b>36w</b> 4,000 lm (Dim) <b>10ACw</b> 1,065 lm (DimLD) <b>15ACw</b> 1,724 lm (DimLD) <b>23ACw</b> 2,540 lm (DimLD)	<b>2</b> 3000K <b>4</b> 4000K  <b>Optional</b> <b>3</b> 3500	<b>W2</b> Gloss White <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze  <b>Optional</b> (see Price List) <b>W1</b> Yolk <b>W3</b> Text White <b>B1</b> Satin Black <b>B2</b> Text Black <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>M13</b> Anod Silver <b>W13</b> Pearl Beige <b>M16</b> Antique Brass <b>P7</b> Brushed Steel <b>P9</b> Brushed Nickel	<b>FSG</b> Frosted Smooth Glass  <b>Optional Lens Material</b> (see Price List) <b>WSA</b> White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i>  <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page <i>(Included with DirectAC Boards only)</i>  <b>OCCHFA</b> Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i>  <b>Battery Backup Options</b> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
<b>PNBC-21-LED</b>			<b>20w</b> 2,325 lm (Dim) <b>36w</b> 4,000 lm (Dim) <b>10ACw</b> 1,065 lm (DimLD) <b>15ACw</b> 1,724 lm (DimLD) <b>23ACw</b> 2,540 lm (DimLD)				



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

