

REBH-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth polycarbonate
- Optional alabaster acrylic (thickness varies by fixture size)

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Canopy mounts to ceiling J-Box with safety cable
- Custom mounting heights available
- Single stem 45-degree swivel standard
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



4 Stem



IS45

REBH-24	REBH-37
Height - 6"	Height - 6"
Width - 24"	Width - 37"
OAH - 24"	OAH - 24"



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: REBH-24-LED-U-84W-3-Z3-BAA-4S

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
REBH-24-LED		U 120 - 277	63w LED / 7354lm (116 lm per watt) 84w LED / 9800lm (116 lm per watt)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	WSP White Smooth Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) (Suspension Systems-See Notes) IS45 -Single Stem 45 degree swivel 4S Four Stem 1S154AC - Single Stem w/Aircraft Cable 4AC - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes
REBH-37-LED			84w LED / 9800lm (116 lm per watt)				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

