

REHW Series LED

Construction:

- Steel housing and chassis
- White textured polycarbonate lens

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounting - See notes below dimensions
- Horizontal or vertical mounting
- ADA compliant
- Optional battery backup
- UL and CUL listed DAMP location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



Type:	
Job Name:	

REHW-315	REHW-326	REHW-415	REHW-426
Height - 15"	Height - 26"	Height - 15"	Height - 26"
Width - 3"	Width - 3"	Width - 4.25"	Width - 4.25"
Depth - 4"	Depth - 4"	Depth - 4"	Depth - 4"

Mounts to 2 x 4 box/opening oriented to match fixture's linear dimension

Mounts to standard J box



ORDERING INFORMATION

Example: REHW-326-LED-O2C-3-T6-WTP

REHW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v)
315-LED	O1C	9	1210	0-10v	NO	Optional 3 3500K		Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	90CRI Consult Factory	
415-LED	O1C	9	1210	0-10v	NO				Optional Voltage	
326-LED	O2C	18	2420	0-10v	NO				-347V Input voltage to 347v	
426-LED	O2C	18	2420	0-10v	NO			Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel	Battery Backup Options (415 & 426 Series only) BB10 10 Watts (1170lm) for 90-Minutes	



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

