

# REKW Series LED

## Construction:

- Steel housing and chassis
- White textured polycarbonate lens

## Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

## Notes:

- Mounting - See notes below dimensions
- Horizontal or vertical mounting
- ADA compliant
- Optional battery backup
- UL and CUL listed DAMP location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components



Type:	
Job Name:	



<b>REKW-315</b>	<b>REKW-326</b>	<b>REKW-415</b>	<b>REKW-426</b>
Height - 15"	Height - 26"	Height - 15"	Height - 26"
Width - 3"	Width - 3"	Width - 4.25"	Width - 4.25"
Depth - 4"	Depth - 4"	Depth - 4"	Depth - 4"

Mounts to 2 x 4 box/opening oriented to match fixture's linear dimension

Mounts to standard J box



WALL

CEILING

PENDANT

OUTDOOR

## ORDERING INFORMATION

Example: REKW-326-LED-U-21W-3-T6-WTP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
<b>REKW-315-LED</b> <b>REKW-415-LED</b>		<b>U</b> 120- 277v	<b>11w</b> LED / 1175lm (106 lm per watt)	<b>2</b> 3000K <b>4</b> 4000K  <b>Optional</b> <b>3</b> 3500K	<b>B1</b> Satin Black <b>T6</b> Pewter <b>W2</b> Gloss White <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze  <b>Optional Finishes</b> (see Price List) <b>W1</b> Yolk <b>W3</b> Text White <b>B2</b> Text Black <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>W13</b> Pearl Beige <b>P2</b> Brushed Alum <b>P9</b> Brushed Nickel	<b>WTP</b> White Textured Polycarbonate	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% <b>(Included)</b>         <b>Battery Backup Options</b> (415 & 426 Series only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
<b>REKW-326-LED</b> <b>REKW-426-LED</b>			<b>21w</b> LED / 2450lm (117 lm per watt)				



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

