

RERH-LED

Construction:

- Steel housing and chassis
- Diffuser is white smooth acrylic
- Optional alabaster acrylic

Light Source:

- LED

Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights available
- Single stem (1S45) 45-degree swivel standard
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Shown with 4 Stem and optional AHA Diffuser



WALL

CEILING

PENDANT


OUTDOOR

RERH-24-LED	RERH-30-LED	RERH-36-LED
Height - 6"	Height - 8"	Height - 8"
OAH - 24"	OAH - 30"	OAH - 36"
Width - 24.75"	Width - 30"	Width - 36"

ORDERING INFORMATION

Example: RERH-24-LED-U-126W-3-Z1-AHA-1S45

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
RERH-24-LED		U 120 - 277	36w LED / 4,000lm 63w LED / 7,350lm 84w LED / 9,800lm 95w LED / 11,025lm 126w LED / 14,700lm	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black T6 Pewter W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige	WSA White Smooth Acrylic Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 to 10v) 120 - 277 volts / Dimming to 10% OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet (Suspension Systems-See Notes) IS45 -Single Stem 45 degree swivel 4S Four Stem 1S154AC - Single Stem w/Aircraft Cable 4AC - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord
RERH-30-LED RERH-36-LED			36w LED / 4,000lm 63w LED / 7,350lm 84w LED / 9,800lm 126w LED / 14,700lm 168w LED / 19,600lm 189w LED / 22,050lm				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

